



handles & catches

# handles and catches

- Our products are machined from high-tech stainless alloys and finished to sub-micron accuracy with precision polishing processes that earn them the title of Deck-Jewellery.
- Monitor handles and catches are secured with Monitor's jacking-ring system, offering a robust locating function.
- Most handles and catches are designed to be maintained in situ.


### 70mm FITTINGS

Part Nos.

15206

Name

70mm Stay-put latch.



### **Description**

Lever-actuated Stainless deadbolt. Lift handle to draw bolt; press handle to close. Weight 435g approx.

#### Details


Mounts thru 60mm hole. 20-30mm bulkhead thickness. Secured with supplied backing plate.





8925 8925-DC 70mm Slam-shut latch.


Simple press-to-close catch with 20mm or 32mm striker-plate offset. Lift lever to open; press hatch closed to secure. Weight 450g approx.

Mounts thru 60mm hole. 20-30mm bulkhead thickness. Secured with supplied backing plate and striker plate.









EL8925

Ø 70 mm

Ø 60 mm

70mm Slam-shut catch with lock.

20.5mm (excluding backplate)

70mm Slam-shut catch securable with included hex key.
Weight 465g approx.

Same specifications and operations as regular Slam-shut catch, but with additional locking device accessible through finger-hole.



## 80mm FITTINGS

Part Nos.

### Name

15022 80mm C

80mm Compression handle with central lock.

### Description

Stylish. Simple. Robust locking. Rotating Compression Lever swings into place and compresses hatch seal with lever action. Key lockable. Weight 1.1kg approx.

### Details

80mm deck footprint. Requires 72mm cutout. Suitable for 10-47mm panel thickness. User–adjustable compression

rate.



15022-E

80mm Compression handle with emergency Safety Release.

Ø 80mm 54mm

80mm Compression handle with Emergency Release safety facility preventing accidental entrapment. Rotating Compression Lever swings into place and compresses hatch seal with adjustable compression rate. Key lockable. Weight 1.1kg approx.

80mm deck footprint. Suitable for 10-47mm panel thickness. Requires 72mm cutout. Emergency release lever identifiable from inside.



Part Nos.

Ø 80mm

**Ø** 66mm

15022-CC

54mm

Name

80mm handle with internal Release Mechanism suitable for crew greas.

**Description** 

Simple spring-loaded sliding bolt releases locking pin internally. Handle can be opened and closed from

outside as normal. Key lockable from outside.


**Details** 

Suitable for 10-47mm panel thickness. Requires 72mm cutout. No adjustment ability. Bolt rotates at fixed depth.

Weight 1.35kg approx



80mm Vertical hatch handle with central lock.



Vertical Handle for front face application. Draws lid to frame. Rattle-proof and waterproof installation.

Weight 1.1kg approx.

Seal compression rate of 9mm. Locking pin rotates on 57mm open radius. Suitable for 10-47mm panel thickness. Requires 72mm cutout.





80mm Vertical hatch handle with central lock. Long reach model.




Longer reach allows handle to be situated further from the edge. Weight 1.13kg approx.



Additional length locking arm rotates on 57mm open radius. Seal compression rate of 9mm. Suitable for 10-47mm panel thickness. Requires 72mm cutout. Key lockable.


2114-F

80mm Hatch Handle (Flush Top).



80mm Compression Handle with additional deluxe shutter offering seamless flush appearance.

Discreet key locking top face for added security. Weight 900g approx.



Seal compression rate of 13mm. Cramping beam rotates on 65mm radius. Suitable for 10-47mm panel thickness. Requires 72mm cutout. Key lockable.




2114-F-HK

Ø 80mm

Ø 66mm

As above, but with hex key.



As above Weight 900g approx.



As above.

## 100mm FITTINGS

47mm

### Part Nos.

2115-F/-DR

### Name

100mm Hatch Handle (Flush Top or Deep Reach)



### **Description**


100mm flush compression-handle with deluxe shutter to ensure the minimalist flush look and top-mounted key locking to secure hatches and doors. Comfortable grip for three or four fingers to confidently handle heavy panels. Weight 1.18kg approx.

### Details

Fits through 92mm hole to suit 30-55mm panel thickness. Cramping beam rotates on 65mm radius. Two clamping depth options: 65 and 83mm. Seal compression rate of 13mm. Key lockable.

2115-F-CC

100mm Hatch Handle (Crew Cabin) + Customised length shaft.





Modified 100mm flush compressionhandle with deluxe shutter to ensure the minimalist flush look and topmounted key locking. Designed to

allow two-way access so that a locked hatch can be opened from within. Weight 1.18kg approx.

Fits through 92mm hole to engage a catch plate at 67mm depth.\* Internal dead-bolt allows easy release from inside, even whilst locked

\*Alternative depths are available upon request



Monitor Marine Fittings are engineered to be as durable as possible.

We choose our metals and production processes to ensure that the product you fit is truly exceptional, so from our high-load alloys to chemical treatments every step of the process is controlled by craftsmen.

Monitor Marine products are precision engineered then laboriously hand-finished, polished, then inspected and buffed, with at least three separate processes to ensure our uncompromising finishes.

We offer, as standard, a finish exceeding EN 10088-2:2014 where all visible surfaces are mirror-polished on the user-facing parts, but for truly exceptional cases Monitor Marine can, upon request, offer an unparalleled level of luxury.

Our Superyacht Finish is an intensive treatment where we hand-finish **all** the above-deck surfaces.

### Also available in the range:

- Multi-Purpose Plug-in Connectors
- 70mm SnapShut Latches
- 70mm StayPut Latch
- 70mm Finger Pull / Mini Pad Eye
- 80mm Hatch Handles
- 80mm Vertical Hatch Handles
- 100mm Hatch Handles
- Deck Drains
- 100mm Bayonet Deck Filler System
- 100mm System 5 Deck Fillers
- Retractable Cleats and Pull-Up Cleats
- Helicopter Tie-Downs
- Maintenance Kit



## LEAVING OTHERS IN OUR WAKE









### **Monitor Marine International**

4 Merse Road, North Moons Moat, Redditch Worcestershire B98 9HL UK

> **T** +44 (0)1527 61243 **F** +44 (0)1527 66836 **E** mmi@b-hepworth.com

